

STD-45G/P

Emergency Eye/Face Wash - Plumbed in

Pedestal mounted emergency eye/face wash available with stainless steel pipework.

This ANSI compliant model has an integral lid to protect the bowl and diffusers against dust and debris.

Designed to be quick and easy to operate with high flow rate aerated diffusers for improved washing.



Specifications

MATERIALS OF CONSTRUCTION	
EYE/FACE WASH BOWL/LID	Acrylic capped ABS
PEDESTAL	Stainless steel
PIPEWORK AND FITTINGS	Stainless steel with 150lb medium wall tubulars and fittings
SERVICES	
WATER INLET	1¼" Female BSP
DESIGN OPERATING PRESSURE	2.0 to 6 BAR G (29 to 87 PSI)
TEST PRESSURE	10.3 BAR G (149 PSI)
MINIMUM FLOW RATES	12 litres/minute minimum (3 US Gallons)
ENVIRONMENTAL OPERATING TEMPERATURE	
MINIMUM AMBIENT OPERATING TEMPERATURE	5° C (41° F)
MAXIMUM AMBIENT OPERATING TEMPERATURE	35° C (95° F)
OPERATIONAL	
EYE/FACE WASH OPERATION	Pull lid forward to operate
WEIGHTS and DIMENSIONS	
DIMENSIONS - STANDARD ORIENTATION (WxDxH)	320mm (12.6in) x 464mm (18.3in) x 1175mm (46.3in)
WEIGHT (NO OPTIONS)	10kg (22lb)

STD-45G/P

Emergency Eye/Face Wash - Plumbed in

